

# MANUAL PUMPS

## Rapidflo™

The GT RAPIDFLO™ is a high performance rotary impeller pump suitable for transferring diesel, ULP, aviation fuels, kerosene & light oils (up to SAE30). The RAPIDFLO™ is capable of transfer rates of 800ml per revolution (up to 100L.min depending on viscosity) from 60-205L drums and tanks.



Robust aluminium housing  
screwed together for ease of  
service and maintenance

Lockable handle and nozzle  
holder for security

High flow rate with close  
to one litre per revolution

Built in strainer

2.4m(8'ft) anti-static  
rubber hose compatible  
with un-leaded petrol  
and aviation fuel\*

Three piece suction  
tube with sliding  
bung adapter to suit  
various size drums



	GT-01 - rapidflo™	GT-01-BD - rapidflo™
<b>Pump output</b>	0.8L/rev (typical delivery rate 100L/min (26 US GAL))	
<b>Action</b>	bi-lobe rotary	bi-lobe rotary
<b>Hose</b>	2.4m (8'ft) anti-static rubber hose	2.4m (8'ft) anti-static rubber hose
<b>Drum size</b>	60L - 205L (16 - 54gal)	60L - 205L (16 - 54gal)
<b>Drum adapter</b>	2" sliding	2" sliding
<b>Lockable handle</b>	✓	✓
<b>Nozzle holder</b>	✓	✓
<b>Built in strainer</b>	✓	✓
<b>Compatible fluids</b>	diesel, ULP, aviation fuels, kerosene, lubricating oils to SAE30	bio diesel, kerosene and lubricating oils to SAE30

Note\* - Users of aviation fuels must check material compatibility with the fuel product they are using. Note<sup>1</sup> Subject to Macnaught warranty terms and conditions, see inside back cover.  
 Note<sup>2</sup> Parts available for 10 years from deletion or upgrade of model.

## Rotary vane pump

An economical rotary pump designed to dispense diesel, kerosene and lubricating oils up to 20 L (5 US gal) per minute from 60 L (16 US gal) to 205 L (55 US gal) drums.

Nozzle holder to stop siphoning between uses

Sliding bung adaptor to handle both 205L (54gal) & 60L (16gal) drums



## Litrestroke™

The LITRESTROKE™ is a hand operated, lever action piston pump for dispensing diesel, kerosene, ULP and light oils (up to SAE30) from 60-205L (16-54gal) drums or tanks. The LITRESTROKE™ delivers 1L (1qrt) per stroke and up to 40L(10gal)/min which makes it suitable for most common fuel transfer applications.

**10 YEARS**  
MACNAUGHT WARRANTY\*

1L(1qrt) per stroke

Robust steel construction

Lockable handle

Two-piece suction tube allows both 205L (54gal) & 60L (16gal) drums to be used

2.4m(8'ft) antistatic hose

Nozzle to suit ULP tanks

Nozzle receiver to keep the hose secure between jobs



	RVP-01 (rotary vane oil pump)	HP-01 (lever action fuel pump)
<b>Pump output</b>	Typical delivery rate 20L(5gal)/min	1ltr/stroke (Typical delivery rate 40L(10.5gal)/min)
<b>Action</b>	rotary	reciprocating
<b>Hose</b>	1.8m(6'ft) PVC/Nitrile hose	2.4m(8'ft) anti-static rubber hose
<b>Drum size</b>	60L - 205L (16-54gal)	60L - 205L (16-54gal)
<b>Drum adapter</b>	2" sliding	2" built in
<b>Lockable handle</b>	✓	✓
<b>Nozzle holder</b>	✓	✓
<b>Built in strainer</b>	✓	✓
<b>Fully serviceable</b>	✓	✓
<b>Warranty<sup>1</sup></b>	10 years	10 years
<b>Parts guarantee<sup>2</sup></b>	10 years	10 years
<b>Compatible fluids</b>	diesel, kerosene and lubricating oils to SAE 90	diesel, petrol, lubricating oils to SAE 30

Note<sup>1</sup> Subject to Macnaught warranty terms and conditions, see inside back cover.

Note<sup>2</sup> Parts available for 10 years from deletion or upgrade of model.