

BOP20 BATTERY OPERATED PUMP-5 Gallon



Simple yet clever, the BOP20 is the industry's first 5 Gallon 18V Rechargeable Oil Pump
Safer with no spills, no funnels and no fatigue using hand pumps. Oils up to 140W / ISO680.

Easy portable Powerhead

Single Powerhead for multiple pump stems

Lithium-ion Battery and Charger

18V rechargeable 2.0Ah battery delivers up to 40 gallons per charge

Drainback Adapter

To drain back oil residue back to the drum *available Dec 2020

New modular concept

Sealed wetted parts for zero contamination

Adjustable suction tube



Kit Contents

Pump stem, powerhead, hose & gun assembly, battery pack and charger.

Pump Stem Contents

Pump stem, hose & gun assembly.



BOP20
BATTERY OPERATED PUMP



Easy control nozzle
Simple single handed 'on demand' flow nozzle

5ft hose



Applications:

Mobile Service, Forklift, Heavy Equipment, Vehicle Service, Farm and AG, Gearbox, Compressor, Elevator, Marine, Mining, Turbine, Crane, Truck and Bus, Windmill, Plant Machinery and General Industrial Oiling Uses

FEATURES & BENEFITS

- On demand flow control
- Sealed wetted parts - zero contamination
- Separate Powerhead - multiple oils with one Powerhead
- Adaptors to suit most workshop fluid containers
- Safety lockout carry handle for simple Powerhead transfer
- No more pumping by hand to reduce fatigue

TECHNICAL SPECIFICATIONS

- 18V rechargeable 2.0Ah battery
- Pail Sizes: Nominal 5 gallon (BOP20)
- Battery - 2.0Ah Li-ion
- Charger - 45 min fast charge

BOPSTD - 1 GPM+ low-mid weight oils at 68F
BOPHV - 1.5GPM+ heavy weight oils at 68F

BP20X-OLA
Pump Stem suitable
for oils up to
90W/ ISO220

BP20X-OHA
Pump Stem suitable
for heavy oils up to
140W/ ISO680

BP20X-ALA
Pump Stem suitable
for ATF

BP20X-COA
Pump Stem suitable for
Premix and Concentrate



LOW-MID
VISCOSITY
OILS



MID-HIGH
VISCOSITY
OILS



ATF
COMPATIBLE



COOLANT
COMPATIBLE



Part Number	BP20S-OLU	BP20X-OLA	BP20S-OHU	BP20X-OHA	BP20X-ALA	BP20X-COA
Description	BOP20 STD Kit	BOP20 STD Pump Stem	BOP20HV Kit	BOP20HV Pump Stem	ATF Pump Stem	Coolant Pump Stem
Delivery rate*	Up to 1 GPM**	Up to 1 GPM**	1.5+ GPM**	1.5+ GPM**	Up to 1.5 GPM	Up to 1.6 GPM
Oil Drum size	5 GAL	5 GAL	5 GAL	5 GAL	5 GAL / 16 GAL	5 GAL
Hook colour	Black	Black	Yellow	Yellow	Red	Green
On demand flow control	✓	✓	✓	✓	✓	✓
Discharge Hose diameter	1/2"	1/2"	3/4"	3/4"	1/2"	1/2"
Portable Power-head	✓	✗	✓	✗	✗	✗
Self-Priming	✓	✓	✓	✓	✓	✓
Safety lockout carry handle	✓	✓	✓	✓	✓	✓
Sealed Wetted parts	✓	✓	✓	✓	✓	✓
Compatible fluids	Suitable for Oils up 90W / ISO220		Suitable for Heavy Oils up 140W /ISO680		ATF	Coolant
Rechargeable Battery	2.0Ah Li-Ion	✗	2.0Ah Li-Ion	✗	✗	✗
Charger	45min fast	✗	45min fast	✗	✗	✗
Warranty ¹	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year

** The delivery rates depend on the type, viscosity the temperature of the fluid.

Recommended to be used with:



Metergun Assembly PN# BP-MG or BP-MGHV

BOP20HV Optional Hose Lengths with Nozzle
: 10ft PN# BP-HV10FT
20ft PN# BP-HV20FT

BOP20/60 Spare Battery PN# BPB-20AH